

# AERA Car

Your signature scent  
 for every vehicle.  
 Quiet, finely dosed  
 and fully automatic.



## HIGHLIGHTS

- ✓ Cold-air diffusion without heat or water
- ✓ Fits any cup holder, sleeve included
- ✓ Starts on movement, stops 10 min after standstill
- ✓ All abbeo scent worlds or your signature scent

## ADDED VALUE

**The first impression starts as guests step in:** they take their seat and the scent is already there. Subtle, even and without spray bursts. This makes **the same scent as in the lounge** part of the transfer.

 10 intensity levels

 Motion sensor

 USB-A & USB-C

 Whisper-quiet 20 dBA

## THE TECHNOLOGY · COLD-AIR DIFFUSION

1

### Insert the cartridge

The 8 ml scent cartridge simply plugs into the device.

2

### Diffuse the oil

The nebulising head atomises the pure fragrance oil without heat.

3

### Ultra-fine mist

Droplets under 1 µm form a fine scent mist.

4

### Evenly distributed

The interior is scented subtly and consistently within a short time.

**approx. 350 h**

runtime per cartridge at medium setting

**5.7 m<sup>3</sup>**

vehicle interior, from compact car to van

**100 %**

personal support, service & refills from Switzerland



VIP transfer

Limousine service

Hotel shuttle

Chauffeur services

Premium rental cars

Company fleets

Showroom vehicles

Other vehicles

## FIVE SCENT WORLDS

FRESH

NATURE

ELEGANT

ENERGY

WARM

Or your own **signature scent** for lounge, reception and vehicle.

## TECHNICAL DATA

| Feature              | AERA Car                                                   |
|----------------------|------------------------------------------------------------|
| Type                 | Single nebulising head                                     |
| Cartridge            | 8 ml · approx. 350 h at medium setting                     |
| Droplet size         | typically below 1 µm                                       |
| Coverage             | up to 5.7 m <sup>3</sup> vehicle interior                  |
| Settings · Pause     | 10 intensity levels · 30 s pause cycle                     |
| Noise level          | 20 dBA at 1 m                                              |
| Power supply         | 5 V / 500 mA · USB-A, USB-C adapter                        |
| Dimensions · Weight  | Device Ø 92 x 112 mm, 266 g · Cartridge Ø 40 x 68 mm, 40 g |
| Housing              | PC/ABS                                                     |
| Operating conditions | -20 to 50 °C, < 85 % rel. humidity                         |
| Approvals            | UL listed; CE, UKCA, RoHS, REACH                           |

